
May 28, 2012



Product Safety Alert

CSA Group Warns of Counterfeit CSA mark on Wire Connector

Toronto, May 14, 2012 – CSA Group is notifying consumers and retailers that a wire connector originally manufactured by Shenzhen Hongyu Electrical Co., Ltd., is being counterfeited by an unknown company. The connector identified below bears a counterfeit CSA mark and has not been evaluated by CSA Group to the applicable CSA standard, and it is unknown if the product complies with safety requirement for Canada. Please contact the point of sale to facilitate a return and/or exchange.

Legitimate Manufacturer:

Shenzhen Hongyu Electrical Co., Ltd.
15th Building, 3rd Industrial Area
Heshuikou, Gongming Town, Guangming New District
Shenzhen City, Guangdong Province, China

Identification:

On the product - The product bears a counterfeit CSA mark and a trademark of Shenzhen Hongyu Electrical Co., Ltd., as well as model number 'P3'.

On the packaging - The packaging has a counterfeit trademark of Shenzhen Hongyu Electrical Co., Ltd., and model number 'P3'.

May 28, 2012

Photo of the product:



| | | | | |
|--|----------------------------|--|---|---|
|  | | SHENZHEN HONGYU ELECTRICAL CO., LTD | | ISO 9001 Registered Quality Control System |
| Wire Connectors Model P3 | | | Qty. 500 pcs | |
| To be sold only with installation instructions Instructions: | | 使用本產品前，務必詳閱使用說明書，並遵照使用。 使用說明： | | |
| 1. Turn off power before installing or removing connectors. 2. Strip wires 5/16" (7.9 mm). For #16 and smaller wires, strip 3/8" (9.5 mm). 3. Pre-twisting unnecessary, hold stripped wires together with ends even. Lead stranded wires slightly. 4. Align any frayed strands or conductors. 5. Push wires into connector and screw on until two twists are visible in wires. | | 1. 裝配或拆除接線頭前，先關閉電源或拔掉插頭。 2. 剝線 5/16" (7.9 mm); #16 及小於 #16 多股電線剝線 3/8" (9.5 mm)。 3. 修整岔開及磨損各芯線或導體。 4. 勿須預絞電線，握住電線對齊剝線端，輕導多股電線。 5. 把電線插入接線頭內，扭轉接線頭直到電線上形成兩個結。 | | |
| For use with copper to copper conductor Temperature Rating: 105°C (221°F) Max. Voltage Rating: 600V Max. building wiring; 1000V Max. in fixtures and signs | | 適用在銅線對銅線之配線 額定溫度：最高 105°C (221°F) 額定電壓：建築配線最高 600V；設備及招牌最高 1000V | | |
| Listed as a PRESSURE-TYPE wire connector on the following Solid and/or Stranded wire combinations: | | 列名為壓力型接線頭，適用下列單股及/或多股線徑組合： | | |
| Voltage Rating 600V Max.: | | | | |
| 2 #16 | 1 #14 w/1 to 3 #20 or #22 | 2 #16 w/1 #18 | 1 #18 w/3 or 4 #22 | |
| 2 to 4 #18 | 1 #16 w/1 or 2 #18 | 2 #16 w/1 or 2 #20 | 1 or 2 #18 w/1 #20 w/1 #22 | |
| 1 #14 w/1 #16 | 1 #16 w/1 #18 w/1 #22 | 2 #16 w/1 to 3 #22 | 2 #18 w/1 or 2 #20 or #22 | |
| 1 #14 w/1 #16 w/1 #18 | 1 #16 w/1 to 3 #20 or #22 | 1 #18 w/2 to 4 #20 | 3 #18 w/1 #20 or #22 | |
| 1 #14 w/1 or 2 #18 | 1 or 2 #16 w/1 #20 w/1 #22 | | | |
| Voltage Rating 300V Max.: | | | | |
| 1 or 2 #14 | 1 #14 w/4 #20 | 3 #16 w/1 or 2 #20 or #22 | 1 #20 w/4 #22 | |
| 3 or 4 #16 | 2 #14 w/1 #18 | 4 #16 w/1 #20 or #22 | 2 #20 w/2 or 3 #22 | |
| 5 #18 | 2 #14 w/1 to 3 #20 or #22 | 1 #18 w/1 #20 | 3 #20 w/1 or 2 #22 | |
| 3 to 5 #20 | 1 #16 w/4 #18 | 1 #18 w/5 #22 | 4 #20 w/1 #22 | |
| 1 #14 w/1 #16 w/1 #18 | 2 #16 w/2 or 3 #18 | 4 #18 w/1 #20 or #22 | 3 #22 Sol w/2 #22 Str | |
| 1 #14 w/2 #16 | 2 #16 w/3 #20 | 3 #18 w/2 #20 or #22 | 5 #22 Sol or Str | |
| 1 #14 w/3 #18 | 3 #16 w/1 #18 | 2 #18 w/3 #22 | | |
| | | | ID Code: "1"  | |